

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD**

GRADE STABILIZATION STRUCTURE

(No.)

CODE 410

DEFINITION

A structure used to control the grade and head cutting in natural or artificial channels.

establishes the policy for Natural Resources Conservation Service personnel in giving assistance to applicants for water rights, construction permits, or approval of water projects as required by State Law.

SCOPE

This standard applies to all types of grade stabilization structures, including a combination of earth embankments and mechanical spillways and full-flow or detention-type structures. This standard also applies to channel side-inlet structures installed to lower the water from a field elevation, a surface drain, or a waterway to a deeper outlet channel. It does not apply to structures designed to control the rate of flow or to regulate the water level in channels (587).

Landowners shall be advised that the construction of any structure may require a permit from the U.S. Army Corps of Engineers in accordance with Section 404 of the Clean Water Act. Information and applications may be obtained from the Corps of Engineers Regulatory Office in Bismarck (Tel. 255-0015).

The structure must be designed for stability after installation. The crest of the inlet must be set at an elevation that stabilizes upstream head cutting.

PURPOSE

To stabilize the grade and control erosion in natural or artificial channels, to prevent the formation or advance of gullies, and to enhance environmental quality and reduce pollution hazards.

Embankment dams. Class (a) dams that have a product of storage times the effective height of the dam of 3,000 or more, those more than 35 ft in effective height, and all class (b) and class (c) dams shall meet or exceed the requirements specified in Technical Release No. 60 (TR-60).

See Section 520.21, National Engineering Manual, for definition of classes of dams.

CONDITIONS WHERE PRACTICE APPLIES

In areas where the concentration and flow velocity of water require structures to stabilize the grade in channels or to control gully erosion. Special attention shall be given to maintaining or improving habitat for fish and wildlife where applicable.

Class (a) dams that have a product of storage times the effective height of the dam of less than 3,000 and an effective height of 35 ft or less shall meet or exceed the requirements specified for ponds (378).

The effective height of the dam is the difference in elevation, in feet, between the emergency spillway crest and the lowest point in the cross section along the centerline of the dam. If there is no emergency spillway, the top of the dam is the upper limit.

DESIGN CRITERIA

Prior to design of this practice, procedures as set forth in the NRCS General Manual-450, Part ND481 and ND482, will be reviewed. This

<p>Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact the Natural Resource Conservation Service.</p>

Pond size dams. If mechanical spillways are required, the minimum capacity of the principal spillway shall be that required to pass the peak flow expected from a 24-hour duration design storm of the frequency shown in Table 1, less any reduction because of detention storage.

The principal spillway capacity should be increased if the emergency spillway will not have a well vegetated, stable grade to the downstream channel.

TABLE 1. DESIGN CRITERIA FOR ESTABLISHING MINIMUM CAPACITY FOR POND SIZE DAMS

Maximum Dr Area	Effective Height of Dam	Storage	Frequency <u>1/</u>	
Acres	Feet	Ac. Ft.	Pr Spwy Year	Total Year
200	20 - 35	<50	2	50
400	20 or less	<50	2	25
400	20 - 35	<50	5	50
600	20 or less	<50	5	25
>600	35 or less	--	10	50

1/ 24 hr. duration storm.

If the effective height of the dam is less than 20 ft and the emergency spillway has a stable grade throughout its length with no overfalls and has good vegetation along its reentry into the downstream channel, the principal spillway capacity may be reduced but can be no less than 80 percent of the 2-year frequency, 24-hour duration storm.

If criteria values exceed those shown in Table 1 or the storage capacity is more than 50 acre-ft, the 10-year frequency, 24-hour duration storm must be used as the minimum principal spillway design storm.

Grade stabilization structures with a settled fill height of less than 15 ft and 10-year frequency, 24-hour storm runoff less than 10 acre-ft, shall be designed to control the 10-year frequency storm without overtopping. The mechanical spillway, regardless of size, may be considered in design and an emergency spillway is not required if the combination of storage and mechanical spillway discharge will handle the design storm. The embankment can be designed to meet the requirements for water and sediment control basins (638) rather than the requirements for ponds (378).

Full-flow open structures. Drop, chute, and box inlet drop spillways shall be designed

according to the principles set forth in the Engineering Field Manual for Conservation Practices, the National Engineering Handbook, and other applicable NRCS publications and reports. The minimum capacity shall be that required to pass the peak flow expected from a design storm of the frequency and duration shown in Table 2, less any reduction because of detention storage. If site conditions exceed those shown in Table 2, the minimum design 24-hour storm frequency is 25 years for the principal spillway and 100 years for the total capacity. Structures must not create unstable conditions upstream or downstream. Provisions must be made to insure reentry of bypassed storm flows.

Toe wall drop structures can be used if the vertical drop is 4 ft or less, flows are intermittent, downstream grades are stable, and tail water depth at design flow is equal to or greater than one-third of the height of the overfall.

The ratio of the capacity of drop boxes to road culverts shall be as required by the responsible road authority or as specified in Tables 2 or 3, as applicable, less any reduction because of detention storage, whichever is greater. The drop box capacity (attached to a new or existing culvert) must equal or exceed the culvert capacity at design flow.

TABLE 2. DESIGN CRITERIA FOR ESTABLISHING MINIMUM CAPACITY OF FULL-FLOW OPEN STRUCTURES

Maximum Dr Area	Vertical Drop	Frequency 1/ Structure	Total
Acres	Feet	Yr	Yr
1200	5 or less	5	10
2200	10 or less	10	25
All others		25	100

1/ 24 hr. duration storm.

TABLE 3. DESIGN CRITERIA FOR ESTABLISHING MINIMUM CAPACITY OF SIDE-INLET DRAINAGE STRUCTURES

Maximum Dr Area	Vertical Drop	Receiving Channel Depth	Frequency 1/ Structure	Total
Acres	Feet	Feet	Year	Year
400	0 - 5	0 - 10	Drainage Curve	--
1200	5 - 10	10 - 20	Drainage Curve	10
2200	0 - 10	0 - 20	Drainage Curve	25
All others			Drainage Curve	50

1/ 24 hr. duration storm.

Island-type structures. If the mechanical spillway is designed as an island-type structure, its minimum capacity shall equal the capacity of the downstream channel. For channels with very small drainage areas, the mechanical spillway should carry at least the 2-year, 24-hour storm or the design drainage curve runoff. The minimum emergency spillway capacity shall be that required to pass the peak flow expected from a design storm of the frequency and duration shown in table 2 for total capacity without overtopping the headwall extensions of the mechanical spillway. Provision must be made for safe reentry of bypassed flow as necessary.

Side-inlet drainage structures. The design criteria for minimum capacity of open-weir or pipe structures used to lower surface water from field elevations or lateral channels into deeper open channels are shown in Table 3. The minimum principal spillway capacity shall equal the design drainage curve runoff for all conditions. If site condition values exceed those

shown in Table 3, the 50-year frequency storm shall be used for minimum design of total capacity.

Landscape resources. In highly visible public areas and those associated with recreation, careful considerations should be given to landscape resources. Landforms, structural materials, water elements, and plant materials should visually and functionally complement their surroundings. Excavated material and cut slopes should be shaped to blend with the natural topography. Shorelines can be shaped and islands created to add visual interest and valuable wildlife habitat. Exposed concrete surfaces may be formed to add texture or finished to reduce reflection and to alter color contrast. Site selection can be used to reduce adverse impacts or create desirable focal points.

General criteria. Earth embankment and emergency spillways of structures for which criteria are not provided under the standard for

ponds (378) or in TR-60 must be stable for all anticipated conditions. If earth spillways are used, they must be designed to handle the total capacity flow indicated in Tables 2 or 3 without overtopping the dam. The foundation preparation, compaction, top width, and side slopes must ensure a stable dam for anticipated flow conditions. Discharge from the structure shall be sufficient that no crop damage results from flow detention.

Necessary sediment storage capacity must equal the expected life of the structure, unless a provision is made for periodic cleanout.

The earth embankment pond structures are potentially hazardous and precautions must be taken to prevent serious injury or loss of life. Protective guardrails, warning signs, fences, or lifesaving equipment shall be added as needed.

If the area is used for livestock, the structures, earthfill, vegetated spillways, and other areas should be fenced as necessary to protect the structure. Near urban areas, fencing may be necessary to control access and exclude traffic that may damage the structure or to prevent serious injury or death to trespassers.

Protection. The exposed surfaces of the embankment, earth spillway, borrow area, and other areas disturbed during construction shall be seeded or sodded as necessary to prevent erosion. If climatic conditions preclude the use of vegetation, nonvegetative coverings such as gravel or other mulches may be used.

PLANS AND SPECIFICATIONS

Plans and specifications for installing grade stabilization structures shall be in keeping with this standard and shall describe the requirements for applying the practice to achieve its intended purpose.

PLANNING CONSIDERATIONS FOR WATER QUANTITY AND QUALITY

Quantity

1. Effects on volumes and rates of runoff, evaporation, deep percolation and ground water recharge.
2. Effects of the structure on soil water and resulting changes in plant growth and transpiration.

Quality

1. Ability of structure to trap sediment and sediment-attached substances carried by runoff.
2. Effect of structure on the susceptibility of downstream stream banks and stream beds to erosion.
3. Effects of the proposed structure on the movement of dissolved substances to ground water.
4. Effects on visual quality of downstream water resources.